

HSS-SENSE[®] X4000 Ex

Explosion Proof, Industrial Acoustic Imaging Camera

Specification

Acoustic Parameters

Acoustic Measurements	128 Low Noise MEMS Microphones, Real-time Sound Visualization
F. O. V.	70°
Dynamic Range	> 120dB
Bandwidth	2kHz – 65kHz, Adjustable
Frame Rate	25 FPS
Measuring Distance	0.3 m to 130 m
Functions	Partial Discharge PD & Noise Positioning Gas Leak Location

Physical & Battery Data

Dimension	316 x 196 x 106 mm (12.4 x 7.7 x 4.1 inch)
Weight	1.1 kg (2.42 lbs)
Battery Capacity	7.2 V, 6700 mAh
Duration	~4 Hours
Charging	USB Type-C interface USB PD Protocol (Power Delivery Protocol)
Power (Capacity factor)	Max. Power 20W, Single charge 16W Max

Environment Parameters

Working Condition	-10°C to +50°C, 10% to 95% non-Condensing
Storage Temperature	-20°C to +40°C
charging Temperature	+10°C to +40°C

User Interface

Screen	Size: 7", 1024 x 600, Color: 24-bit RGB, Brightness: 1000cd/m ³
Input	Capacitive Touchscreen
Video Resolution	1640 x 1234 Video
Video Frame Rate	25 FPS (Max)
Image Frame Rate	30 FPS (Max)

HSS-SENSE[®] X4000 Ex

Explosion Proof, Industrial Acoustic Imaging Camera

Communication & Storage

External Storage	64 GB SD Card
Internal Storage	8 GB, Emergency Storage Only
Data Storage Format	.jpg & .mp4

Camera

F. O. V.	70°
Focal Length	3.04 mm (Fixed)
Pixels	8 million
Built in Battery	6 Wh Li-ion Battery
Warranty	1 Years Limited Warranty 5 Years after-sales service

Under the OEM contract, the quality of the device is closely monitored by High Sense Solutions Inc

High Sense Solutions Inc.

The contents are subject to change without prior notice.



HIGH SENSE SOLUTIONS Inc.

Manufacturer of Subsurface Detection Systems and Utility Instrument

Head-Office:

Unit 23, 35 West Pearce St., Richmond Hill, ON, L4B 3A9, Canada

www.highsensesolutions.ca

sales@highsensesolutions.ca

@high_sense_solutions

Tel: (+1) 905 597 23 41

(+1) 647 588 6020

www.highsensesolutions.ca

sales@highsensesolutions.ca

@high_sense_solutions

